



9x19 Luger FMJ

9 g / 139 gr

Cost effective CIP-approved deformation round.

Provides maximum stopping power.

Preserves the weapon's service life

Application:

Excellent choice for home defense and for law enforcement with. Ideal for service and for outdoor training.

All components are produced to perform seamlessly together for perfect functioning in all common types of weapons.

Performance:

Term of reference	C.I.P.
Temperature range	-20°C to +52°C
Mean case mouth pressure (bar)	max. 2350
Muzzle velocity (m/s)	370
Muzzle energy (J)	616,05
Accuracy	D100% ≤ 100mm at 25m

Cartridge:

Projectile	FMJ, 9 g / 139 gr
Projectile material	CuZn alloy jacket with lead core
Primer / propellant	Standard / Double base powder
Case material	CuZn alloy
Article number	Tbd.

Packaging:

50 rds./cardboard box, 1 000 rds./cardboard box

Technical specification and numerical data are given as an indication only and are of no contractual nature.
version 30. Aug. 2021



RUAG Hungarian Ammotec Inc

Address: Belső gyártelep 1002/35. hrsz., H-3332 Sirok, Hungary

Postal address: Po. Box 9 Sirok, Hungary HU-3332

Phone: +36 36 561 300 / E-mail: info@mfsammunition.com

www.mfs-ammunition.com