



9x19 Luger FMJ-FP

10 g / 154 gr

*CIP-approved round minimizes exposure to lead.
Reliable in extreme environmental conditions.
Preserves the weapon's service life. Low lead
exposure. Extreme high stopping power.*

Application:

Excellent choice for home defense and law enforcement .

All components are produced to perform seamlessly together for perfect functioning in all common types of weapons.

Performance:

Term of reference	C.I.P.
Temperature range	-54°C to +52°C
Mean case mouth pressure (bar)	max. 2350
Muzzle velocity (m/s)	290
Muzzle energy (J)	421
Accuracy	D100% ≤ 80mm at 25m

Cartridge:

Projectile	FMJ-FP, 10 g / 154 gr
Projectile material	CuZn alloy jacket with lead core
Primer / propellant	Standard / Double base powder
Case material	CuZn alloy
Article number	Tbd.

Packaging:

50 rds./cardboard box, 1 000 rds./cardboard box

Technical specification and numerical data are given as an indication only and are of no contractual nature.
version 30. Aug. 2021



RUAG Hungarian Ammotec Inc

Address: Belső gyártelep 1002/35. hrsz., H-3332 Sirok, Hungary

Postal address: Po. Box 9 Sirok, Hungary HU-3332

Phone: +36 36 561 300 / E-mail: info@mfsammunition.com

www.mfs-ammunition.com