



9x19 Luger Subsonic FMJ-FP

10 g / 154 gr

Subsonic ammunition with FMJ-FP bullet. Minimal acoustic profile to maintain the element of surprise.

Heavy bullet yields excellent target effect.

Reliable in extreme environmental conditions. Reliable in extreme environmental conditions.

Application:

Excellent choice for missions in special needs and for IPSC shooting or for regular training.

All components are produced to perform seamlessly together for perfect functioning in all common types of weapons.

Performance:

Term of reference	MCMOPI
Temperature range	-54°C to +52°C
Mean case mouth pressure (bar)	max. 2350
Muzzle velocity (m/s)	290
Muzzle energy (J)	421
Accuracy	D100% ≤ 80mm at 25m

Cartridge:

Projectile	FMJ-FP, 10 g / 154 gr
Projectile material	CuZn alloy jacket with lead core
Primer / propellant	Standard / Double base powder
Case material	CuZn alloy
Article number	Tbd.

Packaging:

50 rds./cardboard box, 1 000 rds./cardboard box

Technical specification and numerical data are given as an indication only and are of no contractual nature. version 30. Aug. 2021



RUAG Hungarian Ammotec Inc

Address: Belső gyártelep 1002/35. hrsz., H-3332 Sirok, Hungary

Postal address: Po. Box 9 Sirok, Hungary HU-3332

Phone: +36 36 561 300 / E-mail: info@mfsammunition.com

www.mfs-ammunition.com